



### Package Contents:

- Vehicle camera recorder
- Suction cup mounting bracket (Adjustable)
- Two warning stickers
- Cigarette lighter power cable (10ft)
- USB cable
- User's manual

### Key Specifications:

<b>LCD size</b>	1.5" TFT LCD
<b>Image sensor</b>	Digital HD color CMOS
<b>Viewing angle</b>	120°A+ grade high-resolution ultra wide-angle
<b>Language for options</b>	English/Deutsch/French/Spanish/Italian/Portugal/Traditional Chinese/Simplified Chinese/Pyccknn/ Japanese
<b>Video resolution</b>	1920x1080FHD, 1440x1080P, 1280x720P, 848x480P, VGA640x480P.& QVGA320x240P
<b>Video/Photo formats</b>	AVI/JPEG
<b>Recording video format</b>	M-JPEG
<b>Photo pixels</b>	1.0M
<b>SD slot</b>	Micro SD card (supports up to 32GB, class 6 or above)
<b>Overwrite</b>	Yes
<b>Microphone</b>	Built-in (Menu: On/Off)
<b>Speaker</b>	Built-in
<b>Recording frame rate</b>	30fps
<b>Video recording mode</b>	*Auto record when the ignition is turned on and stop when engine is turned off (with car cigarette lighter cable connected) *Manual record by pressing REC button *Video Motion Detection recording
<b>Shooting mode (photo)</b>	Single, 2s timer, 5s timer, 10s timer, & Burst Mode (5 consecutive shots)
<b>Frequency</b>	60Hz/50Hz
<b>TV standard</b>	NTSC/PAL
<b>USB port</b>	USB 2.0
<b>PC mode (via USB)</b>	Mass Storage or PC Camera
<b>Power supply</b>	Input: DC12V-24V, Output: 5VDC / 500mAh
<b>Rechargeable battery</b>	3.7V / 200 mAh (Charging time: 2 hrs. Recording time: 1 hr)
<b>Camera size (LxWxH)</b>	2.6"x1.6"x1.2"(without bracket)
<b>Operating temperature</b>	-10°C to 50°C (14°F-122°F)
<b>Non-Operating temperature</b>	-20°C to 65°C (-4°F-149°F)
<b>Operating humidity</b>	≤85% RH
<b>Operation system</b>	Windows 2000, XP, Vista, 7, & 8 / MAC OS 10.7 or above (SD card)