

ClearCam

Wi-Fi Interference Free Mini Wireless
Indoor Color Camera Kit w/Audio

SecurityMan



Wi-Fi
Interference Free



**Easy
Installation**

Features:

- Easy to setup and use
- Perfect for monitoring around your home or business
- Wireless video direct to your TV or recorder
- High quality picture and sound transmitting and receiving
- No interference from crowded 2.4GHz devices
- Stronger wall penetration than 2.4GHz/5.8GHz wireless transmission
- Video transmission goes up to 330ft clear line of sight or 100ft indoor
- Battery operable camera for temporary usage (2-3hrs)
- Flexible channel switch camera design
- Two-channel receiver supports up to two wireless cameras

Package Content:

- Wireless Color Camera (SM-8009) with bracket
- Wireless Receiver (SM-7034)
- AV Cable
- 8V AC Adapter x 2
- 9V Battery
- Battery Clip

Camera (SM-8009) Specifications

Image Sensor	1/4-inch CMOS
Effective Pixels	510x492(NTSC)
Horizontal Resolution	380 TV Lines
Minimum Illumination	5 lux
Auto Electronic Exposure Time	1/60-1/1500
Lens Mount	F=6.2mm pinhole /F2.5 IR filter
View Angle	60 degree
Transmission Frequency	FM 906MHz, 924MHz (2-ch)
Transmission Power	2mW
Bandwidth	10 MHz
Microphone	Built-in
Audio Carrier Frequency	4.5±0.02 MHz
Audio Carrier Amplitude	-25±5 dBc
Power Supply	8±0.25v DC
Consumption Current	55~70 mA
Operation Temperature(°C/°F)	-10~+50/+14~+122
Storage Temperature (°C/°F)	-40~+85/-40~+185
Operation Humidity	15%~85% RH
Dimensions (LxWxH)	43.7 mm×22.5mm×22.5mm 1.72" x 0.88" x 0.88"
Weight	17g/0.6oz

Receiver (SM-7034) Specifications

Receiving Frequency	ISM 906MHz & 924MHz (2 CH, auto-loop/manual)
Intermediate Frequency	480 MHz
Frequency Stabilization	+/- 100 ppm
Antenna	50ohm SMA
Receiving Sensitivity	<-85 dBm
Video Output	1.0V +/- 0.15 Vpp S/N>38dB
Audio Output	600 ohm
Power Supply	8V DC
Power Consumption	190mA
Dimension (WxLxH)	3.1" x 3.6" x 0.8"
Weight	240g/8.5oz