

# ClockCam

## Wi-Fi Interference Free Wireless Wall Clock Hidden Camera Kit



COLOR



DO IT YOURSELF



WIRELESS RANGE

UP TO 150FT



Camera

**Wi-Fi**  
Interference Free

The ClockCam is designed for users who want to discreetly monitor their visitors, strangers, babysitters, and business activities. It includes a wireless receiver and a wireless camera hidden in a functional wall clock. It can be installed in seconds, hassle free of running long video cable. Simply mount the clock at a desired location, connect the power of the clock-camera, to receiver, and then connect the receiver to a monitor for live view, or connect to a recorder for recording. It is a perfect security product for homes and small businesses.

### Features:

- Do-it-yourself, easy to setup and use
- Hidden wireless color camera built-in functional wall-clock
- No interference from crowded 2.4GHz & 5.8GHz frequencies including Wi-Fi (wireless network) device
- Video transmission goes up to 330ft clear line of sight or 100ft indoor
- Add more wireless receivers (one channel, 900MHz) for multi rooms monitoring (no multi cameras)

### Package Contents: (G.W. 3.2lbs)

- 1 x Wall Clock Camera (ClockCam-T)
- 1 x Receiver W/ Antenna (ClockCam-R)
- 1 x AV Cable (for receiver)
- 2 x Warning Stickers
- 2 x Power Adapters
- 1 x User Manual

### Applications:

- Discreetly monitor with fully functional design
- Monitor childcare, know your children are safe for peace of mind
- Monitor your valuables, home, business, office

### Specifications:

Wall-Clock Camera (ClockCam-T)	
Image Sensor	1/4 Inch CMOS, Color
Effective Pixels	510(H) x 492 (V)
Signal System	NTSC
Viewing Angle	Vertical 35 Degree/Horizontal 46 Degree
Transmission Frequency	FM, 900MHz (one channel, 906MHz)
Clock type	Quartz Wall-Clock (Durable plastic glass)
Dimensions/Shaft Length	14.3 (W) x 1.75 (D) / 12mm
Power	Clock: 1.5VDC(AA Battery, not included)
	Camera: AC 100-240V 6DVC 800mA
Operating Temperature	-10 ~ +50(Degree C) / +14 ~ +122(DegreeF)

Receiver (ClockCam-R)	
Audio/Video Output	1 RCA/ 1RCA
Antenna Type	SMA (87dBm sensitivity)
Wireless Receiving Frequency	ISM, 900MHz (one channel, 906MHz)
Dimensions(WxDxH)	4 x 3 x 1
Operating Temperature	-10 ~ +50 (Degree C)
Power	+14 ~ +122 (Degree F)
	AC 100-240V 6VDC 800mA