

DigioutAir

Digital Wireless Outdoor/Indoor Color Camera Kit with Audio and Night Vision



DO IT YOURSELF



DIGITAL WIRELESS



WEATHER RESISTANT



COLOR



NIGHT VISION



AUDIO



Wi-Fi
Interference Free

Go digital with your wireless security needs; the simplest way to secure your home and business. **DigioutAir** is a do-it-yourself digital security camera kit designed for easy installation and operation. In comparison to the traditional analog wireless technology running on 900MHz, 2.4GHz, and 5.8GHz, the 2.4GHz digital wireless technology provides three key advantages; stronger signal strength which provides longer transmission distance (indoor/clear-line-of-site: 200ft/490ft v.s.100ft/300ft), digital signal which is interference free from crowded wireless analog devices (Wi-Fi routers, Bluetooth devices, cordless/cell phones, and other digital wireless band), and privacy which is worry free of signal interceptions from neighborhood.

Package Contents:

- 1 x Digital wireless outdoor/indoor camera with antenna and sun visor
- 1 x Digital wireless receiver with antenna and docking stand
- 2 x Power adapters (for camera and receiver)
- 1 x AV cable
- 1 x Camera mounting bracket
- User's manual and screws

Features:

- Do-it-yourself (D.I.Y) easy to setup and use digital wireless camera kit
- Weatherproof camera housing for outdoor and indoor applications
- Wireless transmission up to 200ft between walls and up to 490ft in clear line of site
- No Wi-Fi interference; no interference from crowded analog 900MHz/2.4GHz/5.8GHz/6.0GHz devices
- Camera with built-in infrared LEDs for night vision up to 50ft (B/W)
- Built-in microphone for audible recording up to 20ft away
- AV output RCA interface from receiver to monitor for live display or to a recorder
- Digital wireless pairing camera and receiver, worry-free of signal interception
- Supports up to 4 sets of digital wireless camera/receiver (CH1-CH4) to a location
- One receiver supports up to four digital wireless cameras (switching one camera at a time)
- Video signal loss alert notification

Key Specifications:

SM-703DT (Camera)	Image Sensor	1/4" CMOS Color
	Resolution	510 x 492 pixels (NTSC)
	Viewing Angle	35 degree
	Weatherproof Rating	IP65
	Night Vision Range	Up to 50ft / 15m (B/W)
	Audio	Microphone built-in (audio monitoring up to 20ft)
	Minimum Illumination	3 Lux/F1.2 (IR off); 0 Lux (IR on)
	Pairing Button	1
	IR LEDs	24 LEDs
	Power Supply	DC 5V / 1.5A
	Dimensions	3.5" x 2.4" x 2.4"
SM-451DR (Receiver)	Pairing Button	1
	Channel Button	1 CH button (Select CH1-CH4)
	AV Output	1 x Video out (RCA); 1 x Audio out (RCA)
	Power Supply	DC 5V / 800mA
	Dimensions	4.2" x 2.7" x 0.9"
Wireless	Stand	1 x docking stand
	Frequency	ISM 2400 - 2480 MHz (CH1/CH2/CH3/CH4)
	Transmission power	17 dBm
	Receiver Sensitivity	≤ -85dBm
	Modulation	GFSK
	Antenna	Omni 3dBi
	Transmission Distance	Up to 490 ft (150m) clear line of site; up to 150ft (indoor)
	Operating Temperature	-20°C to 60°C (-4°F-140°F)
Operating Humidity	20% -80% RH	